

# WORKSHOP EASA 2010

## Runway surfaces: evaluation of contamination

Technical guide

**Jonathan GERTHOFFERT**  
French Technical Center for Civil Aviation

Ressources, territoires et habitats  
Énergie et climat  
Développement durable  
Prévention des risques  
Infrastructures, transports et mer

Présent  
pour  
l'avenir



Direction générale de l'Aviation civile, Service technique de l'aviation civile

Ministère de l'Écologie, de l'Énergie, du Développement durable et de l'Aménagement du territoire



# Introduction

---

- Study “operational friction”
  - Good information not always provided
  - Friction measuring devices not always properly used
- Technical guide in progress
  - To point out regulations and best practices
  - To give technical information on using friction measuring devices
- Based on current regulations, tools and methods

# Regulations

---

- ICAO annexes 6, 14 and 15
- Airport Information Publication AD 1.2
- French regulations
  - Arrêté du 14 mars 2007 relatif aux conditions d'homologation et aux procédures d'exploitation des aérodromes (CHEA)
  - Arrêté du 6 mars 2008 relatif aux inspections de l'aire de mouvement d'un aérodrome
  - Arrêté du 3 juin 2008 relatif aux services d'information aéronautique
  - Arrêté du 18 juillet 2008 relatif aux procédures pour les organismes rendant les services de la circulation aérienne aux aéronefs de la circulation aérienne générale (RCA)

# *French regulations*

---

- Agreement signed between ATC and airport operators to provide aeronautical information
- Contaminated runways: Airport Operators are responsible for
  - Regularly inspecting traffic area
  - Collecting data about runway surface condition, especially about
    - Nature of contamination
    - Extent of contamination
    - Depth of contamination
    - Friction measurements
  - Providing information to ATC

# *Preventive actions*

---

- Weaknesses of the infrastructure
  - Reporting areas propitious for contaminant accumulation
  - Reporting all reference data, such as functional friction values
  - Etc...
- Debriefings from previous events
  - Areas where contaminant accumulated
  - Evolution of deposits, especially after de-icing/de-snowing operations
  - Slippery areas
  - Operational friction values
  - Etc...
- Training
- Device calibration and maintenance

# *Information to report*

---

- Nature of contamination
  - Vocabulary and definitions
- Extent of contamination
  - Assessed either visually or with the aid of friction device
- Depth of contamination
  - For water, dry snow, wet snow and slush only
  - Assessment
  - Reporting
- Friction measurements
  - Conditions acceptable to use friction devices
  - Use of friction devices
  - Interpretation and reporting
  - A part of an overall surface condition assessment

# *Information to report*

---

- Any additional information essential for operating
  - Rapid exit taxiways surface conditions
  - Taxiways surface conditions
  - Snow banks
  - Cleared runway length/width
  - Obscured lights
  - Etc...

# Ways of reporting

- Reporting runway surface conditions through
  - SNOWTAM
  - METAR
  - ATIS
  - Etc...

Detailed content		Template(s)	
State of the runway (C) <sup>16</sup>	Runway designator (M)	R nn[L]/ or Rnn[C]/ or Rnn[R]/	
	Runway deposits (M)	n or/	CLRD//
	Extent of runway contamination (M)	n or/	
	Depth of deposit (M)	nn or//	
	Friction coefficient or braking action (M)	nn or//	

METAR format

SNOWTAM	(Serial number)	→
(AERODROME LOCATION INDICATOR)	A)	→
(DATE/TIME OF OBSERVATION (Time of completion of measurement in UTC))	B)	→
(RUNWAY DESIGNATORS)	C)	→
(CLEARED RUNWAY LENGTH, IF LESS THAN PUBLISHED LENGTH (m))	D)	→
(CLEARED RUNWAY WIDTH, IF LESS THAN PUBLISHED WIDTH (m; if offset left or right of centre line add "L" or "R"))	E)	→
(DEPOSITS OVER TOTAL RUNWAY LENGTH (Observed on each third of the runway, starting from threshold having the lower runway designation number))	F)	→
NIL — CLEAR AND DRY 1 — DAMP 2 — WET or water patches 3 — RIME OR FROST COVERED (depth normally less than 1 mm) 4 — DRY SNOW 5 — WET SNOW 6 — SLUSH 7 — ICE 8 — COMPACTED OR ROLLED SNOW 9 — FROZEN RUTS OR RIDGES		→
(MEAN DEPTH (mm) FOR EACH THIRD OF TOTAL RUNWAY LENGTH)	G)	→
(FRICTION MEASUREMENTS ON EACH THIRD OF RUNWAY AND FRICTION MEASURING DEVICE MEASURED OR CALCULATED COEFFICIENT or ESTIMATED SURFACE FRICTION 0.40 and above — GOOD — 5 0.39 to 0.36 — MEDIUMGOOD — 4 0.35 to 0.30 — MEDIUM — 3 0.29 to 0.26 — MEDIUMPOOR — 2 0.25 and below — POOR — 1 9 — unreliable — UNRELIABLE — 9 (When quoting a measured coefficient, use the observed two figures, followed by the abbreviation of the friction measuring device used. When quoting an estimate, use single digit)	H)	→
(CRITICAL SNOWBANKS (If present, insert height (cm)/distance from the edge of runway (m) followed by "L", "R" or "LR" if applicable))	J)	→
(RUNWAY LIGHTS (If obscured, insert "YES" followed by "L", "R" or both "LR" if applicable))	K)	→
(FURTHER CLEARANCE (If planned, insert length (m)/width (m) to be cleared or if to full dimensions, insert "TOTAL"))	L)	→
(FURTHER CLEARANCE EXPECTED TO BE COMPLETED BY ... (UTC))	M)	→
(TAXIWAY (If no appropriate taxiway is available, insert "NO"))	N)	→
(TAXIWAY SNOWBANKS (If more than 60 cm, insert "YES" followed by distance apart, m))	P)	→
(APRON (If unusable insert "NO"))	R)	→
(NEXT PLANNED OBSERVATION/MEASUREMENT IS FOR) (month/day/hour in UTC)	S)	→
(PLAIN-LANGUAGE REMARKS (Including contaminant coverage and other operationally significant information, e.g. sanding, de-icing))	T)	}<≡

SNOWTAM format



# Summary

Assessment		Reporting			
Nature	Depth	Extent	Nature	Depth	Friction
Damp	-	YES	YES	NO	NO*
Wet	<3mm	YES	YES	NO	
Flooded	>3mm	YES	YES	YES	
Dry snow	<20mm	YES	YES	NO	
	>20mm			YES	
Wet snow	<3mm	YES	YES	NO	
	>3mm			YES	
Slush	<3mm	YES	YES	NO	
	>3mm			YES	
Compacted snow	-	YES	YES	NO	YES
Frost					
Ice					
Wet ice					

\*Friction assessment can always be performed as a part of an overall surface conditions assessment but values should not be published on liquid contaminants