



ICAO ENGINE EXHAUST EMISSIONS DATA SHEET

SUBSONIC ENGINES

ENGINE IDENTIFICATION: PW4x62 BYPASS RATIO: 4.6
UNIQUE ID NUMBER: 1PW059 PRESSURE RATIO (π_{00}): 31.9
COMBUSTOR: Phase 3
ENGINE TYPE: TF RATED THRUST (F_{00}) (kN): 275.8

REGULATORY DATA ** DATA SUPERSEDED ** SEE FOLLOWING UID FOR REVISED DATA: 12PW102

CHARACTERISTIC VALUE:	HC	CO	NO _x	SMOKE NUMBER
D _p /F ₀₀ (g/kN) or SN	6.6	39.2	66.7	13.0
AS % OF ORIGINAL LIMIT	33.8	33.2	64.2	72.5
AS % OF CAEP/2 LIMIT (NO _x)			80.2	
AS % OF CAEP/4 LIMIT (NO _x)			94.1	
AS % OF CAEP/6 LIMIT (NO _x)			106.2	
AS % OF CAEP/8 LIMIT (NO _x)			123.7	

DATA STATUS

- PRE-REGULATION
x CERTIFICATION
- REVISED (SEE REMARKS)

TEST ENGINE STATUS

- NEWLY MANUFACTURED ENGINES
x DEDICATED ENGINES TO PRODUCTION STANDARD
- OTHER (SEE REMARKS)

EMISSIONS STATUS

x DATA CORRECTED TO REFERENCE
(ANNEX 16 VOLUME II)

CURRENT ENGINE STATUS

(IN PRODUCTION, IN SERVICE UNLESS OTHERWISE NOTED)
- OUT OF PRODUCTION (DATE: -)
- OUT OF SERVICE (DATE: -)

MEASURED DATA

MODE	POWER	TIME	FUEL FLOW	EMISSIONS INDICES (g/kg)			SMOKE NUMBER
	SETTING (%F _{oo})	(minutes)	(kg/s)	HC	CO	NO _x	
TAKE-OFF	100	0.7	2.767	0.08	0.38	37.65	10.1
CLIMB OUT	85	2.2	2.166	0.08	0.51	27.55	7.4
APPROACH	30	4.0	0.708	0.15	1.68	12.78	0.7
IDLE	7	26.0	0.223	3.26	23.96	4.14	0.0
LTO TOTAL FUEL (kg) or EMISSIONS (g)			920	1192	8811	15864	-
NUMBER OF ENGINES				1	1	1	1
NUMBER OF TESTS				3	3	3	3
AVERAGE D _p /F _{oo} (g/kN) or AVERAGE SN (MAX)				4.3	31.9	57.5	10.1
SIGMA (D _p /F _{oo} in g/kN, or SN)							
RANGE (D _p /F _{oo} in g/kN, or SN)							

ACCESSORY LOADS

POWER EXTRACTION 0 (kW)
STAGE BLEED 0 (% CORE FLOW)

AT - POWER SETTINGS
AT - POWER SETTINGS

ATMOSPHERIC CONDITIONS

BAROMETER (kPa)	102
TEMPERATURE (K)	270
ABS HUMIDITY (kg/kg)	0.0015

FUEL

SPEC	Jet A
H/C	1.91
AROM (%)	21

MANUFACTURER: Pratt & Whitney
TEST ORGANIZATION: Pratt & Whitney
TEST LOCATION: Middletown, CT
TEST DATES: 15/01/1993-19/01/1993

NO_x REGULATION PARAGRAPH

x	2.3.2 c) (CAEP/4)
	2.3.2 d) (CAEP/6)
	2.3.2 e) (CAEP/8)

REMARKS

1. Data from X693-20 with Phase 3 reduced pressure loss combustor
2. Certification in accordance with Part III, Chapter 2, of Amendment 7 of ICAO Annex 16 Vol. II.
3. NO_x levels in accordance with Part III, Chapter 2, 2.3.2 d) (CAEP/6)

Compliance with Fuel Venting requirements:

- ('x' if complies, 'PR' if pre-regulation, '-' if information is not available)