



ICAO ENGINE EXHAUST EMISSIONS DATA SHEET

SUBSONIC ENGINES

ENGINE IDENTIFICATION: V2527-A5 SelectOne™ Upgrade Package BYPASS RATIO: 4.8
UNIQUE ID NUMBER: 10IA013 PRESSURE RATIO (π_{00}): 27.1
COMBUSTOR: Floatwall
ENGINE TYPE: MTF RATED THRUST (F_{00}) (kN): 110.3

REGULATORY DATA ** DATA SUPERSEDED ** SEE FOLLOWING UID FOR REVISED DATA: 01P10IA021

CHARACTERISTIC VALUE:	HC	CO	NO _x	SMOKE NUMBER
D _p /F ₀₀ (g/kN) or SN	0.5	28.3	50.9	11.1
AS % OF ORIGINAL LIMIT	2.3	24.0	53.9	48.0
AS % OF CAEP/2 LIMIT (NO _x)			67.4	
AS % OF CAEP/4 LIMIT (NO _x)			81.5	
AS % OF CAEP/6 LIMIT (NO _x)			92.6	
AS % OF CAEP/8 LIMIT (NO _x)			110.6	

DATA STATUS

- PRE-REGULATION
x CERTIFICATION
- REVISED (SEE REMARKS)

TEST ENGINE STATUS

x NEWLY MANUFACTURED ENGINES
- DEDICATED ENGINES TO PRODUCTION STANDARD
- OTHER (SEE REMARKS)

EMISSIONS STATUS

x DATA CORRECTED TO REFERENCE
(ANNEX 16 VOLUME II)

CURRENT ENGINE STATUS

(IN PRODUCTION, IN SERVICE UNLESS OTHERWISE NOTED)
x OUT OF PRODUCTION (DATE: -)
- OUT OF SERVICE (DATE: -)

MEASURED DATA

MODE	POWER SETTING (%F ₀₀)	TIME (minutes)	FUEL FLOW (kg/s)	HC	CO	NO _x	SMOKE NUMBER
TAKE-OFF	100	0.7	1.049	0.03	0.42	23.18	6.9
CLIMB OUT	85	2.2	0.873	0.03	0.44	19.36	7.7
APPROACH	30	4.0	0.328	0.07	2.25	9.74	3.8
IDLE	7	26.0	0.134	0.14	11.96	5.19	1.6
LTO TOTAL FUEL (kg) or EMISSIONS (g)			447	39	2741	5102	-
NUMBER OF ENGINES				2	2	2	2
NUMBER OF TESTS				4	4	4	4
AVERAGE D _p /F ₀₀ (g/kN) or AVERAGE SN (MAX)				0.4	24.8	46.3	9.4
SIGMA (D _p /F ₀₀ in g/kN, or SN)							
RANGE (D _p /F ₀₀ in g/kN, or SN)							

ACCESSORY LOADS

POWER EXTRACTION 0 (kW)
STAGE BLEED 0 (% CORE FLOW)

AT - POWER SETTINGS
AT - POWER SETTINGS

ATMOSPHERIC CONDITIONS

BAROMETER (kPa)	100.4-102.9
TEMPERATURE (K)	268.2-277.7
ABS HUMIDITY (kg/kg)	0.0014-0.00359

FUEL

SPEC	Jet A
H/C	1.91
AROM (%)	17

MANUFACTURER: International Aero Engines
TEST ORGANIZATION: Pratt & Whitney
TEST LOCATION: East Hartford, CT
TEST DATES: 11/12/2008-19/01/2009

NO_x REGULATION PARAGRAPH

	2.3.2 c) (CAEP/4)
x	2.3.2 d) (CAEP/6)
	2.3.2 e) (CAEP/8)

REMARKS

- Engine performance reflects new SelectOne™ package upgrades.
- Certification in accordance with Part III, Chapter 2, of Amendment 6 of ICAO Annex 16 Vol. II.
- NO_x levels in accordance with Part III, Chapter 2, 2.3.2 d) (CAEP/6)

Compliance with Fuel Venting requirements: x ('x' if complies, 'PR' if pre-regulation, '-' if information is not available)