



## ICAO ENGINE EXHAUST EMISSIONS DATA SHEET

## SUBSONIC ENGINES

ENGINE IDENTIFICATION: V2530-A5 SelectOne™ Upgrade Package BYPASS RATIO: 4.6  
UNIQUE ID NUMBER: 04P10IA027 PRESSURE RATIO ( $\pi_{co}$ ): 32.0  
COMBUSTOR: Floatwall  
ENGINE TYPE: MTF RATED THRUST ( $F_{eo}$ ) (kN): 133.0

## REGULATORY DATA

CHARACTERISTIC VALUE:	HC	CO	NO <sub>x</sub>	SMOKE NUMBER
D <sub>p</sub> /F <sub>eo</sub> (g/kN) or SN	0.4	22.2	61.3	11.1
AS % OF ORIGINAL LIMIT	1.9	18.8	59.0	50.5
AS % OF CAEP/2 LIMIT (NO <sub>x</sub> )			73.7	
AS % OF CAEP/4 LIMIT (NO <sub>x</sub> )			86.4	
AS % OF CAEP/6 LIMIT (NO <sub>x</sub> )			97.4	
AS % OF CAEP/8 LIMIT (NO <sub>x</sub> )			113.3	

For non-volatile particulate matter (nvPM) emissions, please refer to the ICAO Engine nvPM Emissions Data Sheet.

## DATA STATUS

- PRE-REGULATION  
x CERTIFICATION  
- REVISED (SEE REMARKS)

## TEST ENGINE STATUS

x NEWLY MANUFACTURED ENGINES  
- DEDICATED ENGINES TO PRODUCTION STANDARD  
- OTHER (SEE REMARKS)

## EMISSIONS STATUS

x DATA CORRECTED TO REFERENCE  
(ANNEX 16 VOLUME II)

## CURRENT ENGINE STATUS

(IN PRODUCTION, IN SERVICE UNLESS OTHERWISE NOTED)

x OUT OF PRODUCTION (DATE: - )  
- OUT OF SERVICE (DATE: - )

## MEASURED DATA

MODE	POWER	TIME	FUEL FLOW	EMISSIONS INDICES (g/kg)			SMOKE NUMBER
	SETTING (%F <sub>oo</sub> )	(minutes)	(kg/s)	HC	CO	NO <sub>x</sub>	
TAKE-OFF	100	0.7	1.325	0.02	0.39	31.43	3.7
CLIMB OUT	85	2.2	1.078	0.03	0.41	23.92	6.6
APPROACH	30	4.0	0.387	0.06	1.65	10.92	5.7
IDLE	7	26.0	0.145	0.12	10.45	5.52	1.4
LTO TOTAL FUEL (kg) or EMISSIONS (g)			517	38	2594	7414	–
NUMBER OF ENGINES				2	2	2	2
NUMBER OF TESTS				4	4	4	4
AVERAGE D <sub>p</sub> /F <sub>oo</sub> (g/kN) or AVERAGE SN (MAX)				0.3	19.5	55.7	9.4
SIGMA (D <sub>p</sub> /F <sub>oo</sub> in g/kN, or SN)							
RANGE (D <sub>p</sub> /F <sub>oo</sub> in g/kN, or SN)							

## ACCESSORY LOADS

POWER EXTRACTION 0 (kW) AT - POWER SETTINGS  
STAGE BLEED 0 (% CORE FLOW) AT - POWER SETTINGS

## ATMOSPHERIC CONDITIONS

BAROMETER (kPa)	100.4-102.9
TEMPERATURE (K)	268.2-277.7
ABS HUMIDITY (kg/kg)	0.0014-0.00359

## FUEL

SPEC	Jet A
H/C	1.91
AROM (%)	17

MANUFACTURER: International Aero Engines  
TEST ORGANIZATION: Pratt & Whitney  
TEST LOCATION: East Hartford, CT  
TEST DATES: 11/12/2008-19/01/2009

NO<sub>x</sub> REGULATION PARAGRAPH

	2.3.2 c) (CAEP/4)
x	2.3.2 d) (CAEP/6)
	2.3.2 e) (CAEP/8)

## REMARKS

- Engine performance reflects new SelectOne™ package upgrades.
- Certification in accordance with Part III, Chapter 2, of Amendment 6 of ICAO Annex 16 Vol. II.
- NO<sub>x</sub> levels in accordance with Part III, Chapter 2, 2.3.2 d) (CAEP/6)

Compliance with Fuel Venting requirements:

x ('x' if complies, 'PR' if pre-regulation, '- ' if information is not available)